




Tipo Type	Dimensioni - Dimensions								Bull. fiss. Bolt Size	BPFT-SA		Cuscinetto Bearing	Peso Weight	BPFT-SB		Cuscinetto Bearing	Peso Weight	Supporto Housing	Coefficienti di carico (N) Load ratings (N)	
	d	a	e	w	m	s	t	f(min)		B ₁	n			B ₁	n				Dinamico C Dynamic C	Statico C ₀ Static C ₀
	mm/inch									mm/inch										
BPFT-SA BPFT-SB 201	12	81	63,5	28,5	14	7,1	4	49	M6	28,6	6,5	SA201	0,26	22	6	SB201	0,23	PFT203	9200	4480
201-8	½	33/16	2½	11/8	9/16	9/32	0,157	159/64	¼	1,1260	0,2559	SA201-8		0,8661	0,2362	SB201-8				
BPFT-SA BPFT-SB 202	15	81	63,5	28,5	14	7,1	4	49	M6	28,6	6,5	SA202	0,26	22	6	SB202	0,23	PFT203	9200	4480
202-9	9/16	33/16	2½	11/8	9/16	9/32	0,157	159/64	¼	1,1260	0,2559	SA202-9		0,8661	0,2362	SB202-9				
202-10	5/8											SA202-10				SB202-10				
BPFT-SA BPFT-SB 203	17	81	63,5	28,5	14	7,1	4	49	M6	28,6	6,5	SA203	0,26	22	6	SB203	0,23	PFT203	9200	4480
203-11	11/16	33/16	2½	11/8	9/16	9/32	0,157	159/64	¼	1,1260	0,2559	SA203-11		0,8661	0,2362	SB203-11				
BPFT-SA BPFT-SB 204	20	90	71,5	33	16	9	4	56	M8	31	7,5	SA204	0,28	25	7	SB204	0,28	PFT204	12200	6300
204-12	¾	35/16	2 13/16	1 19/64	5/8	23/64	0,157	213/64	5/16	1,2204	0,2953	SA204-12		0,9843	0,2756	SB204-12				
BPFT-SA BPFT-SB 205	25	95	76	35	18	9	4	60	M8	31	7,5	SA205	0,36	27	7,5	SB205	0,36	PFT205	13300	7460
205-13	13/16											SA205-13				SB205-13				
205-14	7/8	3¾	253/64	13/8	23/32	23/64	0,157	223/64	5/16	1,2204	0,2953	SA205-14		1,0630	0,2953	SB205-14				
205-15	15/16											SA205-15				SB205-15				
205-16	1											SA205-16				SB205-16				
BPFT-SA BPFT-SB 206	30	113	90,5	40	18	11	5,2	71	M10	35,7	9	SA206	0,58	30	8	SB206	0,55	PFT206	18500	10800
206-17	11/16											SA206-17				SB206-17				
206-18	11/8	47/16	39/16	137/64	23/32	7/16	0,205	251/64	3/8	1,4055	0,3543	SA206-18		1,1811	0,3150	SB206-18				
206-19	13/16											SA206-19				SB206-19				
206-20	1¼											SA206-20				SB206-20				
BPFT-SA BPFT-SB 207	35	122	100	44,5	20	11	5,2	81	M10	38,9	9,5	SA207	0,82	32	8,5	SB207	0,74	PFT207	24500	14600
207-20	1¼											SA207-20				SB207-20				
207-21	15/16	413/16	315/16	1¾	25/32	7/16	0,205	33/16	3/8	1,5315	0,3740	SA207-21		1,2598	0,3346	SB207-21				
207-22	13/8											SA207-22				SB207-22				
207-23	17/16											SA207-23				SB207-23				
BPFT-SA BPFT-SB 208	40	148	119	55	23	13,5	5,8	85	M15	43,7	11	SA208	1,05	34	9	SB208	0,90	PFT208	27700	17000
208-24	1½	513/16	411/16	23/16	29/32	0,531	0,228	3,646	7/16	1,7201	0,4331	SA208-24		-	0,3543	SB208-24				
208-25	19/16											SA208-25				SB208-25				

Disponibile in acciaio inox Supporto: AISI 304 - Cuscinetto: AISI 440C o 420C - Available stainless steel Housing: AISI 304 - Bearing: AISI 440C or 420C.