

Art.-Nr.: 10.01.38.00433



## Technical data

|                    |                         |
|--------------------|-------------------------|
| Weight             | 2.000 kg                |
| Shape fittings     | Straight                |
| Material type      | Foam open, height 20 mm |
| Length L           | 442.00 mm               |
| Width B            | 130.00 mm               |
| Outside diameter D | 32.00 mm                |
| Product family     | FMP                     |
| Arrangement        | 3R18                    |


FMP-SW70 442 3R18 O20 G32

- Integrated control valves at FMP-S (optional)
- Control of vacuum on/off (24V DC, normally open) and blow off on/off (24V DC, normally closed), as well as hose accumulator preload and blower ventilation function with version FMP-S
- Integrated in the end cover
- Electrical connection: M12 plug (4-pole)

Available spare parts: sealing foam (DI-PL), suction cup (SPB2)



Art.-Nr.: 10.01.38.00433

**Design data**

|                    |           |
|--------------------|-----------|
| Length L2          | 402.00 mm |
| Length L           | 442.00 mm |
| Width B            | 130.00 mm |
| Height H1          | 111.00 mm |
| Height H2          | 20.00 mm  |
| Height H           | 70.00 mm  |
| Outside diameter D | 32.00 mm  |
| Length L3          | 90.00 mm  |
| Width B3           | 21.60 mm  |
| Height H3          | 7.70 mm   |
| Height H4          | 5.50 mm   |
| Hole spacing Y1    | 90.0 mm   |
| Valve type         | SW        |
| Height H5          | 41.00 mm  |

Note: Vacuum hose with internal diameter equal to dimension D required. See Technical Data -> Shape

Design data FMP-SW70 442 3R18 O20 G32

**Technical data**

|                                                 |                         |
|-------------------------------------------------|-------------------------|
| Weight                                          | 2.000 kg                |
| Material type                                   | Foam open, height 20 mm |
| Number of suction cells                         | 66                      |
| Required suction capacity for $p_u = -0.25$ bar | 300.0 l/min             |
| Product family                                  | FMP                     |
| Arrangement                                     | 3R18                    |
| Sealing element                                 | Sealing Foam            |
| Suction force at -250 mbar                      | 440.00 N                |

Note: Air consumption: At 5.5 bar compressed air input pressure / Suction force: At a vacuum of -0.25 bar and full occupancy of the gripper with a workpiece typical for the application (wooden board with textured surface) / Required suction capacity: The external vacuum generator used must provide at least the specified suction volume (at the vacuum connection piece of the FMP) at a vacuum of -0.25 bar, but max. 135 % of the specified suction volume



31.12.2027


[WWW.SCHMALZ.COM/10.01.38.00433](http://WWW.SCHMALZ.COM/10.01.38.00433)

Art.-Nr.: 10.01.38.00433

**Ordering Data Accessories 10.01.38.00433**

| Typ                             |                                   | Item number    |
|---------------------------------|-----------------------------------|----------------|
| Cover (complex)                 | ABDK-PROF-10x7x1450-KU-SW-FXP-FMP | 26.07.03.00002 |
| Solenoid valve                  | EMVP 25 24V-DC 3/2 NO/NC          | 10.05.02.00151 |
| Flange plate                    | FLAN-PL 120x85x10 ST FLGR         | 10.01.10.05701 |
| Flexolink                       | FLK G1/2-IG G1/2-AG               | 10.01.03.00175 |
| Suspension, flexible            | FST-FLEX 25 HD1 G1/2-AG G3/8-IG   | 10.01.10.05697 |
| Suspension, flexible            | FST-FLEX 25 HD2 G1/2-AG G3/8-IG   | 10.01.10.05695 |
| Suspension, flexible            | FST-FLEX 50 HD1 G1/2-AG G3/8-IG   | 10.01.10.05687 |
| Suspension, flexible            | FST-FLEX 50 HD2 G1/2-AG G3/8-IG   | 10.01.10.05168 |
| Suspension, flexible            | FST-FLEX 75 HD1 G1/2-AG G3/8-IG   | 10.01.10.05698 |
| Suspension, flexible            | FST-FLEX 75 HD2 G1/2-AG G3/8-IG   | 10.01.10.05696 |
| Suspension, rigid               | FST-STARR 25 HD1 G1/2-AG G3/8-IG  | 10.01.10.05810 |
| Suspension, rigid               | FST-STARR 25 HD2 G1/2-AG G3/8-IG  | 10.01.10.05806 |
| Suspension, rigid               | FST-STARR 50 HD1 G1/2-AG G3/8-IG  | 10.01.10.05809 |
| Suspension, rigid               | FST-STARR 50 HD2 G1/2-AG G3/8-IG  | 10.01.10.05805 |
| Suspension, rigid               | FST-STARR 75 HD1 G1/2-AG G3/8-IG  | 10.01.10.05808 |
| Suspension, rigid               | FST-STARR 75 HD2 G1/2-AG G3/8-IG  | 10.01.10.05803 |
| Flange module                   | MOD-FLAN 120x120 FXP-FMP          | 10.01.21.00244 |
| Mounting set reed switch        | SET fuer-Sensor(FXP/FMP)          | 10.01.38.01194 |
| Mounting set                    | SET FXC-FMC                       | 10.01.21.01291 |
| Mounting set                    | SET FXP-FMP                       | 10.01.21.02407 |
| Mounting set                    | SET FXP-FMP 4NUTSTEIN G20         | 10.01.21.00243 |
| Dust filter                     | STF G1-1/4-IG N                   | 10.07.01.00008 |
| Vacuum gauge                    | VAM 40 V U BAR                    | 10.07.02.00046 |
| Valve unit                      | VENT-EINH 8/6 NC 24V-DC           | 10.01.21.02405 |
| Vacuum hose (meter)             | VSL 42-32 PU-DS-AS TR             | 10.07.09.00036 |
| Vacuum switch (inst)            | VS-MONT 50x15.8x25 VS             | 10.06.02.00343 |
| Vacuum switch (inst)            | VS-MONT 84x21x34.5 VSi-V FMP      | 10.01.38.04053 |
| Vacuum distributor              | VTR-SL 3x RST60 2xD32             | 10.01.43.00013 |
| Hose connector, bent (inst)     | SCHL-AN W 32-79x79x29 FMP         | 10.01.38.00299 |
| Hose connector, straight (inst) | SCHL-AN 32-79x79x40 FMP           | 10.01.38.00298 |
| Sealing plate (inst)            | VRS-PL 79x79x12 SPZ G2-IG         | 10.01.21.01280 |

**Ordering Data Spare Parts 10.01.38.00433**

| Typ                         |                 | Item number    |
|-----------------------------|-----------------|----------------|
| Bellows suction cup (round) | SPB2 40 SI-55 P | 10.01.06.03126 |

**Ordering Data Wear Parts 10.01.38.00433**

| Typ                               |                                   | Item number    |
|-----------------------------------|-----------------------------------|----------------|
| Seal. plate (FXP/FMP/FXP-S/FMP-S) | DI-PL 442x128 3R18 LL-20x7 O20 KE | 10.01.38.00113 |

