

第一生产基地

First Manufacture Base:

(中韩)宁波波特气动元件有限公司

(Sino-Korea)Ningbo bote Pneumatic Co.,ltd

(Sino-Korea)Ningbo Pneumatic Technical Expert Co.,Ltd

地址：浙江省宁波慈溪长河镇长丰工业区

ADD: Changfeng Village Industry Zone Changhe Town Cixi, Ningbo Zhejiang China

国内销售部 (Domestic Trade Dept.)

TEL: 0086-574-23888882 0086-574-63412016

FAX: 0086-574-23688633 0086-574-63412015

国外销售部 (International Trade Dept.)

TEL: 0086-574-23670015

FAX: 0086-574-23688633

邮箱/E-MAIL:ptce@ptce.net

网站/Website: www.ptce.net / www.ptce.en.alibaba.com

邮编/P.C : 315326

第二生产基地

Second manufacture base:

上海蒂豪机电科技有限公司

Shanghai Dihao Mechanical & Electrical Technology Co.,Ltd

地址：上海市翔殷路128号1号楼C座，329-330

ADD: C 329-330 , No.1 Bulding , No.128 XiangYin Road ,Shanghai City. China

国内销售部 (Domestic Trade Dept.)

国外销售部 (International Trade Dept.)

Tel: 0086-021 51613965

FAX: 0086-021 51613953

邮箱/E-MAIL:ptce@ptce.net

网站/Website:www.ptce.net / www.nbptce.cn.alibaba.com

邮编/P.C : 200433



www.ptce.net



**SINO-KOREA
NINGBO BOTE PNEUMATIC
寧波波特氣動元件**

TO BE INTERNATIONAL WELL-KNOWN MANUFACTURER

ISO9001:2000

ISO9001:2000



型号 MODEL
BSL-M5
BSL-01
BSL-02
BSL-03
BSL-04
BSL-06
BSL-10
BSL-12
BSL-14
BSL-20



型号 MODEL
SD-01
SD-02
SD-03
SD-04
SD-06



型号 MODEL
BESL-01
BESL-02
BESL-03
BESL-04



型号 MODEL
BSLM-01
BSLM-02
BSLM-03
BSLM-04
BSLM-06
BSLM-10



型号 MODEL
PSL-01
PSL-02
PSL-03
PSL-04



型号 MODEL
PUS-01
PUS-02
PUS-03
PUS-04

快插 COUPLER



型号(T) MODEL (T)
HOSE STEM
20SH
30SH
40SH



型号(T) MODEL (T)
螺紋(R) Tread(R)
20SM
30SM
40SM



型号(T) MODEL (T)
螺紋(RC) Tread(RC)
20SF
30SF
40SF



型号(T) MODEL (T)
HOSE NUT (T)
20SP
30SP
40SP



型号(T) MODEL (T)
HOSE STEM
20PH
30PH
40PH



型号(T) MODEL (T)
螺紋(R) Tread(R)
20PM
30PM
40PM



型号(T) MODEL (T)
螺紋(RC) Tread(RC)
20PF
30PF
40PF



型号(T) MODEL (T)
HOSE NUT (T)
20PP
30PP
40PP



型号(T) MODEL (T)
HOSE STEM
OSH20
OSH30
OSH40



型号(T) MODEL (T)
螺紋(R) Tread(R)
OSM20
OSM30
OSM40



型号(T) MODEL (T)
螺紋(RC) Tread(RC)
OSF20
OSF30
OSF40



型号(T) MODEL (T)
HOSE NUT (T)
OSN20
OSN30
OSN40

APPLICATIONS

-Used for piping of pneumatic devices.

FEATURES

- Excellent flexibility at low temperatures.
- Light-weight with good tolerance to wear and chemicals.
- Convenient for piping as it has better flexibility than nylon tubes.
- Tubes are available in diverse colors according to the working situation.

SPECIFICATIONS

- Fluid type: Air (No other gases or liquids)
- Working pressure: 0~150PSI/0~9.9Kg/cm² (0~990KPa)
- Negative pressure: -29.5in Hg/-750mmHg (-750Torr)
- Working temperature: 32~140 F/0~60° C
- Applicable Tube: Polyurethane and Nylon

TUBE COLOR CODE

Color	White	Black	Red	Blue	Yellow	Green	Clear	Silver
CODE	WT	BK	RD	BU	YL	GR	CL	SL

PU



型号(外径-内径) MODEL (Outer-Inner)	管(公制) Tube (Metric)	管(英寸) Tube (Inch)
PU 0302		PU 1/8
PU 0402		PU 5/32
PU 0425		PU 3/16
PU 0640		PU 1/4
PU 0850		PU 5/16
PU 0855		PU 3/8
PU 1085		PU 1/2
PU 1280		
PU 1290		
PU 1612		

NA



型号(外径-内径-长度) MODEL (Outer-Inner-Length)	管(公制) Tube (Metric)	管(英寸) Tube (Inch)
NA 0420		
NA 0425		
NA 0640		
NA 0860		
NA 1080		
NA 1290		

FEATURES

A Safe efficient accurate tool for cutting tubing squarely

SPECIFICATIONS

Available Tubing	Polyurethane and Nylon
Cutting Outer Dia	φ3.0-φ12.0
Material	Polyacetal, Stainless steel
Standard Color	Blue



T-C-□
Tube Cut- *
B: Black
BL: Blue
Y: Yellow

吹尘枪 AIR GUNS

PRODUCT CODE

AG — 01 — B
Air Gun Nozzle Color
00-20mm
01-100mm
02-200mm
03-300mm
B: Blue
R: Red

